Reverse Osmosis System

Reverse Osmosis (RO),a water filtration process where drinking water, which contains dissolved solids, is run through a membrane. The water then goes to a storage tank and most of the unwanted inorganic compounds, sediment and other contaminants are flushed down the drain. This form of water treatment is one of the most effective methods for producing high quality drinking water.

Our five stage system produces up to 50 gallons of water per day.

This fully automatic, preassembled system is easy to install and comes with the necessary hardware and fittings.



SPECIFICATIONS

FIVE STAGE PURIFICATION PROCESS:

The first stage:

• Sediment filter (rust, sand, and dirt removal)

The second stage:

 GAC activated carbon (chlorine, unwanted tastes and odor removal)

The third stage:

Activated carbon block filter (most heavy metal removal)

The fourth stage:

 Thin film composite (TFC) membrane (allows water molecules to pass while rejecting dissolved impurities which are flushed down the drain)

The fifth stage:

 Post Carbon (this process enhances and clarifies water prior to delivery)
Available in 1/4" and 3/8

INSTALLATION REQUIREMENTS

The requirements below are necessary for correct installation, proper operation and to validate the warranty:

- A pressure of 40 psi* (276 Kpa**) minimum and 100 psi (689 Kpa) maximum.
- A temperature of 40-100 °F (5-35 °C).
- Maximum total dissolved solids (TDS) 1500 ppm.***
- Installation must comply with existing provincial and local plumbing codes.
- PH level 3-11.

*pounds per square inch **Kilo-Pascal ***parts per million

1175 Stellar Drive, Units 1 & 2 Newmarket, ON L3Y 788 1.888.513.8280

tel: 905.853.1811 fax: 905.853.9004 e-mail: info@rosmosis.com www.rosmosis.com

